

# Stripcoil wagon Shimmns<sup>4</sup>-ttu



## General

Load limits:

	A	B1	B2	C2	C3 C4	D2	D3	D4
S	38,2	38,2	50,0	55,0	58,0	55,0	64,6	68,0
120	00,0 t							

Tare: ca. 22,0 t  
mit Handbremse:  
ca. 22,1 t

R<sub>min</sub>: 35 m

Gauge: TEN-RIV / G1

Axle load: 22,5 t

Ramp angle  
(R=150m): 2,5°

Loading width: max. 2400 mm  
between the  
securing arms:  
352–2.052 mm

## Running Gear

Y25Lsd1 (K)

Wheel diameter: 920 mm

Wheel set type: BA 004

Axle box type: BA 182

Suspension: coil spring

## Brake

Brake type: KE-GP-A 12"

Brake block: Cosid 810

Load braking: MAX 58 t/contin., autom.

Handbrake (20 %): operated from ground

Air reservoir: 100 l

Loading diagram:

cradle	1	2	3	4	5
∅ min mm	1000	800	1000	800	1000
∅ max mm	2200	1650	2650	1650	2200
t max	34 t	17 t	45 t	17 t	34 t

## Draw gear and Buffer

Buffer Endkr/Hub: Cat.C 650 kN/105 mm

Buffer plate  
dimensions: 340 x 450 mm

Draw gear: normal/85t

## Equipment

Tarpaulin with anti-condensate layer

5 Coil cradles with 6mm Tectan (PU)-inlet

4 securing arms by cradle with type "ttu" for narrow band coils, fully adjustable.

## Remarks

TSI

## Load Goods

Sensitive moisture-proof Steel Coils

# Stripcoil wagon Shimmns<sup>4</sup>-ttu

## Appendix to Data Sheet

